



DATA SHEET 38.4V105AH



Model:BE10538CB

Voltage: 38.4V | Capacity: 105Ah | Energy: 4.032KWh

ELECTRICAL SPECIFICATIONS

Nominal Voltage	38.4V
Nominal Capacity	105Ah
Bluetooth Enabled	Yes
Capacity @ 20A	315 min
Efficiency	99%
Self Discharge	1-3% per month
Cell Configuration	1P12S

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H)	13.11" x 10.58" x 10.67"
Weight	77.3 lbs
Terminal Type	M8
Terminal Material	Brass
Case Material	Steel
Enclosure Protection	IP66
Cell Type - Chemistry	Prismatic LiFePO4

DISCHARGE SPECIFICATIONS

Max Continuous Current	250A
Peak Discharge Current	520A±15.6A (30S)
BMS Discharge Current cut-off	260A±7.8A (50S) 520A±15.6A (30S)
BMS Discharge Voltage Cut-Off	30.0V
Recom. Low Voltage disconnect	36.0V
Reconnect Voltage	31.2V
Discharge Temperature Range	-4F < T ≤ 140F

BLUETOOTH FEATURES

Voltage (overall and individual cell voltages)
Remote technical support
Remaining Charge/Discharge Time
Firmware update
Current Cell Temperature
Current Amp Draw
Lifetime Power Cycles

CHARGE SPECIFICATIONS

Recommended Charge Current	5-52A
Maximum charging Current	105Ah
Input Current Cut-off	375A(1S)
Recom. Charge Voltage	30V - 43.8 V
Charge Temperature Range	14F < T ≤ 131F
BMS Charge Voltage Cut-Off	43.8V
Reconnect Voltage	<43.8V

COMMUNICATION

Bluetooth	Bluetooth receiver
BMS languages	CANBUS

SAFETY SPECIFICATIONS

ALL VISIBLE ON THE BOLT ENERGY BATTERY BLUETOOTH APP

Short Circuit	Yes
Low / High Temperature Discharging	Yes
Low / High Temperature Charging	Yes
Over-Current Discharging	Yes
Over-Current Charging	Yes
Pack Under / Over Voltage	Yes
Certifications	UL1642 IEC62619 (Cells) UN38.3 MSDS (Battery)
Shipping Classification	UN 3480 Class 9

