



DATA SHEET 51.2V60AH

Model: 33-51060SB



Voltage: 51.2V | Capacity: 60Ah | Energy: 3.072KWh

ELECTRICAL SPECIFICATIONS

Nominal Voltage	51.2V
Nominal Capacity	60Ah
Bluetooth Enabled	Yes
Capacity @ 20A	180 min
Efficiency	99%
Self Discharge	1-3% per month
Maximum Modules in Parallel	3

DISCHARGE SPECIFICATIONS

Max Continuous Current	185A
Peak Discharge Current	400A±12A (1S)
BMS Discharge Current cut-off	250A±7.5A (30S) 400A±12A (1S)
BMS Discharge Voltage Cut-Off	40V
Recom. Low Voltage disconnect	48V
Reconnect Voltage	41.6V
Discharge Temperature Range	-4F<T≤140F

CHARGE SPECIFICATIONS

Recommended Charge Current	< 30A
Maximum charging Current	60A
Input Current Cut-off	200A
Recom. Charge Voltage	40V - 58.5 V
Charge Temperature Range	32F<T≤131F
BMS Charge Voltage Cut-Off	58.5V
Reconnect Voltage	<58.5V

SAFETY SPECIFICATIONS

ALL VISIBLE ON THE BOLT ENERGY BATTERY BLUETOOTH APP

Short Circuit	Yes
Low / High Temperature Discharging	Yes
Low / High Temperature Charging	Yes
Over-Current Discharging	Yes
Over-Current Charging	Yes
Pack Under / Over Voltage	Yes
Certifications	UL1642 IEC62619 (Cells) UN38.3 MSDS (Battery)
Shipping Classification	UN 3480 Class 9

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H)	12.8" x 12.01 x 10.28"
Weight	72.75 lbs
Terminal Type	M8
Terminal Material	Brass
Case Material	Steel
Enclosure Protection	IP66
Cell Type - Chemistry	Prismatic LiFePO4

BLUETOOTH FEATURES

Voltage (overall and individual cell voltages)
Remote technical support
Remaining Charge/Discharge Time
Firmware update
Current Cell Temperature
Current Amp Draw
Lifetime Power Cycles

COMMUNICATION

Bluetooth	Bluetooth receiver
BMS languages	CANBUS

